

**SLOTTED INDENTED
HEX WASHER HEAD
TYPE "25" TCS**


XXXXSHW25Z

APRIL, 2014

REV 00

PAGE 1 of 1

Nominal Screw Length	Tolerance On Screw Length
Up To & Including 3/4"	-0.03
Over 3/4" to 1-1/2" Inclusive	-0.05
Over 1-1/2"	-0.06



Nominal Screw Size	"D"				"d"		"P"		"S"		"A"		"W"		"H"		"B"		"U"		"J"		"T"			
	Major Diameter		Minor Diameter		Point Diameter	Point Taper Length	Width Across Flats		Width Across Corners	Head Height	Washer Diameter		Washer Thickness		Slot Width		Slot Depth		Max.		Min.		Max.		Min.	
	Max.	Min.	Max.	Min.	Ref.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	
#4-24	0.114	0.108	0.086	0.082	0.079	0.083	0.063	0.188	0.181	0.202	0.060	0.049	0.243	0.225	0.019	0.011	0.039	0.031	0.042	0.025	0.048	0.039	0.053	0.033		
#6-20	0.139	0.132	0.104	0.099	0.095	0.100	0.075	0.250	0.244	0.272	0.093	0.080	0.328	0.302	0.025	0.015	0.054	0.045	0.074	0.052	0.060	0.050	0.080	0.057		
#8-18	0.166	0.159	0.122	0.116	0.112	0.111	0.083	0.250	0.244	0.272	0.110	0.096	0.348	0.322	0.031	0.019	0.067	0.056	0.103	0.077	0.075	0.064	0.111	0.083		
#10-16	0.189	0.182	0.141	0.135	0.130	0.125	0.094	0.312	0.305	0.340	0.120	0.105	0.414	0.384	0.031	0.019	0.084	0.072	0.134	0.100	0.094	0.081	0.168	0.131		
#12-14	0.215	0.208	0.164	0.157	0.152	0.143	0.107	0.312	0.305	0.340	0.155	0.139	0.432	0.398	0.039	0.022	0.067	0.056	0.103	0.077	0.075	0.064	0.111	0.083		
1/4-14	0.246	0.237	0.192	0.185	0.179	0.143	0.107	0.375	0.367	0.409	0.190	0.172	0.520	0.480	0.050	0.030	0.075	0.064	0.111	0.083	0.075	0.064	0.111	0.083		
5/16-12	0.315	0.306	0.244	0.236	0.230	0.167	0.125	0.500	0.489	0.545	0.230	0.208	0.676	0.624	0.055	0.035	0.094	0.081	0.168	0.131	0.094	0.081	0.168	0.131		
3/8-12	0.380	0.371	0.309	0.299	0.293	0.167	0.125	0.562	0.551	0.614	0.295	0.270	0.780	0.720	0.063	0.037										

Standard: ASME B18.6.3

Material: Carbon Steel,

Heat Treat: Case Hardened Rc45 Min.

Finish: Commercial Zinc, Bake & ROHS Compliant Clear Chromate
Per ASTM F1941 Code Fe/Zn 3A

Common Uses:

Increased Bearing Surface w/o Adding A Washer.
Used in painted sheet metal ≤60% of screw dia.; hard plastics, hard woods & aluminum extrusions.